

SLEEVE IT Limited

L124

Sleeve It L124 is manufactured by braiding 'E' Glass yarn. The sleeving is uncoated but has been subjected to a heat process to caramelize the glass yarn size, induce braid roundness and some interyarn bonding. The heat treatment also reduces the fray of the sleeving when cut.

Features:

- Resistance to abrasion
- Range 0.5 - 25.0mm
- Operational temperature -20°C to 220°C
- Maximum temperature 600°C
- Hot splash resistant
- Available in natural

Sizes Available:

- | | | |
|-----------------------|---|-------------------|
| Bore Size 0.5 - 1.5mm | - | Reel Size 500mtrs |
| Bore Size 2.0 - 3.5mm | - | Reel Size 250mtrs |
| Bore Size 4.0 - 8mm | - | Reel Size 100mtrs |
| Bore Size 9.0mm + | - | Reel Size 50mtrs |



All information shown, including illustrations is believed to be reliable. Users, however, should independently evaluate the suitability of the product for their application. Sleeve It makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. In no case will Sleeve It be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Sleeve It specifications are subject to change without notice. In addition Sleeve It reserves the right to make changes in materials and processing, without notification to the buyer, which do affect compliance with any applicable specification.