

**Sleeve It SIGB**

**GLASS FIBRE BRAIDED SLEEVING LIGHTLY IMPREGNATED SILICONE RESIN**

**Features**

- Temperature class: CLASS C
- Continuous working temperature: From -60°C to +350°C. Peak to +400°C (a few hours)
- Dielectric strength: 1 kV
- Flammability: Non flammable
- Good mechanical resistance
- Good resistance to UV
- Resistance to transformer oils according to UTEC 93641
- Good compatibility with class C impregnation varnishes
- Good performance with soldering iron
- Good performance with liquid combustibles, no decomposition
- Flexible
- Non-watertight

**Sizes**

Manufactured diameters	0.5 to 30 mm		
Standard colour:	Light brown (Natural)		
Standard packaging	Coils	Diameter 0.5 to 4 mm	200 m
		Diameter 5 to 12 mm	100 m
		Diameter 14 to 20 mm	50 m
		Diameter 22 to 30 mm	25 m

All information shown, including illustrations is believed to be reliable. Users, however, should independently evaluate the suitability of the Product for their application. Sleeve It makes no warranties as to the accuracy or completeness of the information and disclaims any Liability regarding its use. In no case will Sleeve It be liable for any incidental, indirect or consequential damages arising from the sale, Resale, use or misuse of the product. Sleeve It specifications are subject to change without notice. In addition Sleeve It reserves the right to Make changes in materials and processing, without notification to the Buyer, which do affect compliance with any applicable specification.