

Flexguard Hose Burst

Flexguard hose burst is a high abrasion strength, non toxic and heat resistance woven ballistic Nylon® which protects personnel against hose spray-out failures.

Flexguard Hose Burst stays intact at the highest operating temperature possible for any Nylon®6 - Polycaprolactum abrasion fire sleeve treated with our proprietary heat and flame resistant coating technology.

Easily installed over hoses, cables, tubing or pipes. The bulked material used is entangled which offers excellent leakage containment due to hose failures. Exhibits excellent resistance to UV, atmospheric agents, moisture and ageing, making it ideal for outdoor applications.

Standard format

Inside diameter: from 19mm up to 89mm

Nominal wall thickness: 1.14mm

Method of supply: 50m coil

Colour

Black

MSHA approved



Oil & Fluid Resistance

Gasoline	Very Good
Oil	Very Good
Alcohols	Very Good
Benzene	Very Good
Ether	Very Good
Acetone	Very Good
Diluted Bases	Very Good
Diluted Acids	Good
Mineral & Vegetable Oil	Very Good

Continuous Operating Temperature	126°C (260°F)
Max short term exposure	245°C (473°F)
Molten splash resistance	Not recommended
Flame resistance	Good
Abrasion resistance	Outstanding
Flexibility	Outstanding

All information shown, including illustrations is believed to be reliable. Users, however, should independently evaluate the suitability of the product for their application. Sleeve It makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. In no case will Sleeve It be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Sleeve It specifications are subject to change without notice. In addition Sleeve It reserves the right to make changes in materials and processing, without notification to the buyer, which do affect compliance with any applicable specification.