



SLEEVE IT

LIMITED

SIGB

Glass fibre braided sleeving lightly impregnated silicone resin

Features:

- Temperature class: CLASS C
- Continuous working temperature: From - 60°C to + 350°C.
Peak to + 400°C (a few hours)
- Dielectric strength: 1 kV
- Flammability: Non flammable
- Good mechanical resistance
- Good resistance to UV
- Resistance to transformer oils according to UTEC 93641
- Good compatibility with class C impregnation varnishes
- Good performance with soldering iron
- Good performance with liquid combustibles, no decomposition
- Flexible
- Non-watertight

Sizes:

Manufactured diameters 0.5 to 30 mm

Standard colour: Light brown (Natural)

Standard packaging Coils Diameter 0.5 to 4mm: 200m

Diameter 5 to 12mm 100m

Diameter 14 to 20mm: 50m

Diameter 22 to 30mm: 25m

All information shown, including illustrations is believed to be reliable. Users, however, should independently evaluate the suitability of the product for their application. Sleeve It makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. In no case will Sleeve It be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Sleeve It specifications are subject to change without notice. In addition Sleeve It reserves the right to make changes in materials and processing, without notification to the buyer, which do affect compliance with any applicable specification.

Sleeve It Limited. Syke Mill, Belthorn Road, Belthorn, Blackburn, Lancashire, BB1 2NN.
Tel: 01254 694733 Fax: 01254 691521 Email: sales@sleeveit.co.uk www.sleeveit.co.uk