

TWIST IT GP

Twist It GP is a woven PET wraparound sleeve designed for protecting wire harnesses and cables. The 'spring wrap' action enables application after termination of wires and cables. Installation is efficient and breakouts are quickly produced during harnesses building.

Sizes

- 5mm Black x 50m Coil
- 9mm Black x 50m Coil
- 13mm Black x 50m Coil
- 18mm Black x 50m Coil
- 25mm Black x 25m Coil
- 35mm Black x 25m Coil
- 50mm Black x 25m Coil

Features

- Flexible
- Wraparound - Side Entry
- Zero Halogen
- High Resistance to abrasion
- Range 2 - 30mm
- Operation temperature -50°C to 150°C



Technical Data

| | | |
|-----------------------------|------------------------------|------------------------|
| Specific Gravity | ISO R1183 | 1.38g/cm ³ |
| Tensile Stress | | 650N/sq.mm |
| Tenacity | | 5.3g/d |
| Elongation | | 20% |
| Operating Temperature Range | | -50°C to + 150°C |
| Melt Temperature | | 275°C |
| Low Temperature Flexibility | ASTM D 2671 (4h at -55°C) | No Cracking or Crazing |
| Shrinkage | Water 100°C | 2 - 4% |
| Shrinkage | Air 200°C | 24 - 28% |

All information shown, including illustrations is believed to be reliable. Users, however, should independently evaluate the suitability of the product for their application. Sleeve It makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. In no case will Sleeve It be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Sleeve It specifications are subject to change without notice. In addition Sleeve It reserves the right to make changes in materials and processing, without notification to the buyer, which do affect compliance with any applicable specification.